electron solar corona. This component of the corona, often called the K-corona, is strongly polarized, the direction of the polarization being practically radial. It was successfully detected without eclipse in 1930 by B. Lyot at Pic du Midi with a coronagraph and a visual polarimeter able to detect a percentage of polarization as low as 0.1 per cent. Lyot's observations went as far as $0.35 R_{\odot}$ from the limb.

The new instrument, called the K-coronameter, has been designed to permit observations at a greater distance from the edge of the sun, of the order of 0.5 to $1.0 R_{\odot}$. It is a coronagraph supplemented by a sensitive photoelectric polarimeter. The analyzer of polarization consists essentially of an electrically birefringent crystal excited by an a.c. voltage, a polarizer and a Lallemand photomultiplier. The a.c. signal from the multiplier is fed to a narrow band amplifier with synchronous detection. The band width is of the order of a few cycles per second.

To reduce as much as possible the instrumental polarization, the coronal observations are always made on the axis. Thus, when scanning around the limb, the axis of the instrument describes a cone. A complete scan, at one given distance from the limb, takes 4 minutes. During the scan, a half-wave plate rotating at the speed of 1 round/8 min. keeps the plane of polarization of the light entering the analyzer in a fixed direction.

With a relatively clear sky, Brightness $B_s \sim 10^{-4} B_{\odot}$, it has been possible in Boulder to detect the main features of the corona streamers up to $0.5 R_{\odot}$ and in one case up to $0.66 R_{\odot}$. There is generally a good correlation between the brightness of the green coronal emission line measured with a conventional coronagraph.

It is planned to move the instrument to Climax this summer, at elevation 11,000 feet where better sky conditions prevail, and to make routine observations on clear days during the International Geophysical Year.

The principal development work on this instrument was supported by the U. S. National Committee for the I.G.Y. under a grant from the National Science Foundation; a portion was supported by Radio Corporation of America.

*High Altitude Observatory,
Boulder, Colo.*

Wood, Frank Bradshaw and Blitzstein, William.
The new Flower and Cook Observatory.

This paper describes the facilities and equipment of the new Flower and Cook Observatory.

Located twenty miles west of Philadelphia at an elevation of 500 ft, this replaces the old Flower and old Cook Observatories, and is designed to complement the offices, classroom, library, and laboratory facilities and the Students' Observatory on the University of Pennsylvania campus.

The Observatory contains the $28\frac{1}{2}$ -inch reflector and the 15-inch horizontal refractor with siderostat from the old Cook Observatory. It has a large room serving as office and working library, an electronics workshop, a dark room, an observers' bunk room, and modest cooking facilities.

Instruments in operation include the Pierce pulse-counting photoelectric photometer, a simple d.c. photoelectric photometer, a photoelectric photometer designed especially for scintillation measures, and an experimental infrared photometer using photoconductive cells. The observational work is heavily concentrated on eclipsing binaries.

In addition to formal dedication ceremonies on the evening of June 11, the completion of the Observatory was marked by a two-day symposium on the future of the telescope of moderate size. The papers represented the contributions of 17 astronomers. Dr. Fred Whipple gave a popular lecture on the earth satellite. A final highlight was the award by the University of Pennsylvania of an honorary Doctor of Science degree to Professor Otto Struve.

*Flower and Cook Observatory,
University of Pennsylvania,
Philadelphia, Pa.*

Wood, John A., Jr. Sputtering and the drag coefficient in the regime of free molecular flow.

For artificial satellites or micrometeorites the extent of surface deterioration caused by atmospheric encounter is investigated, on the basis of cathode sputtering theory. The expression used for sputtering efficiency is that presented by F. Keywell, and is based on the concept of sputtering as a momentum-transfer process. For iron micrometeorites, the maximum mass loss attributable to sputtering is found to be ~ 31 per cent of the initial mass in the case of initial velocity 70 km/sec, decreasing linearly to 0 per cent at 30 km/sec, the sputtering threshold energy. Olivine is considered as a typical meteoritic silicate; assuming the heat of sublimation to lie between -436 kcal/mole (heat of formation) and -231 kcal/mole (heat of formation minus energy attributable to Si-O bonds), the sputtering threshold according to G. K. Wehner's rela-